

Package: varmapack (via r-universe)

September 16, 2026

Type Package

Title Burn-in-Free Simulation and Analysis of Gaussian VARMA Models

Version 0.1.2

Description Simulates Gaussian vector autoregressive-moving-average time-series models without a burn-in period by drawing startup shocks from their model-implied conditional distribution. Also provides model test cases, autocovariances, spectral radii, and impulse responses.

License MIT + file LICENSE

Encoding UTF-8

Depends R (>= 4.0.0)

Imports R6, randompack (>= 0.1.10)

LinkingTo randompack

Suggests knitr, rmarkdown, testthat (>= 3.0.0)

VignetteBuilder knitr

Config/testthat/edition 3

RoxygenNote 7.3.2

URL <https://github.com/jonasson2/varmapack>

BugReports <https://github.com/jonasson2/varmapack/issues>

NeedsCompilation yes

Author Kristján Jónasson [aut, cre]

Maintainer Kristján Jónasson <jonasson@hi.is>

Repository <https://jonasson2.r-universe.dev>

Date/Publication 2026-09-15 22:10:02 UTC

RemoteUrl <https://github.com/cran/varmapack>

RemoteRef HEAD

RemoteSha 40808f90c9614347b58ea906052d7d1a4377e61d

Contents

varmapack_autocov	2
varmapack_cov2corr	3
varmapack_model	3
varmapack_testcase	5
varmapack_testcases	6
Index	7

varmapack_autocov	<i>Sample autocovariances of an observed series</i>
-------------------	---

Description

Compute sample autocovariance matrices up to a specified lag for a numeric time-series matrix with variables in rows and observations in columns.

Usage

```
varmapack_autocov(X, maxlag, norm = "ML")
```

Arguments

X	Numeric r by n observed time-series matrix.
maxlag	Largest lag to compute, between zero and n - 1.
norm	Either "ML", which divides every lag by n, or "C", which divides the lag-k co-variance by n - k.

Value

An r by r by maxlag + 1 array. Its k + 1 plane estimates $Cov(x_t, x_{t-k})$.

Examples

```
X <- rbind(1:10, (1:10)^2)
varmapack_autocov(X, maxlag = 2)
```

varmapack_cov2corr	<i>Convert covariances to correlations</i>
--------------------	--

Description

Convert a covariance matrix or sequence of autocovariance matrices to correlations using the marginal standard deviations at lag zero.

Usage

```
varmapack_cov2corr(cov)
```

Arguments

cov	A finite numeric r by r matrix or r by r by $\text{maxlag} + 1$ array. The diagonal entries of its lag-zero matrix must be positive.
-----	--

Value

A numeric array with the same dimensions as cov. Lag-zero diagonal entries are exactly one. Other entries are not clipped to $[-1, 1]$.

Examples

```
cov <- array(c(4, 3, 3, 9, 2, 6, -3, 1.5), dim = c(2, 2, 2))
varmapack_cov2corr(cov)
```

varmapack_model	<i>Create a VARMA or VARMAX model</i>
-----------------	---------------------------------------

Description

Create a model object for simulation of a Gaussian VAR, VMA, VARMA, or VARMAX time series. The object stores model parameters and provides a `$sim()` method for generating one or more independent series.

Usage

```
varmapack_model(A = NULL, B = NULL, C = NULL, Sig, mu = NULL)
```

Arguments

A	Autoregressive coefficient matrices as an r by r matrix or an r by r by p array. NULL gives no autoregressive terms.
B	Moving-average coefficient matrices as an r by r matrix or an r by r by q array. NULL gives no moving-average terms.
C	Exogenous coefficient matrices as an r by d matrix or an r by d by s array. NULL gives a VARMA model rather than VARMAX.
Sig	r by r innovation covariance matrix.
mu	Optional r vector or r by nmu matrix of time-series means. The last mean vector repeats for the rest of each series. Means are not supported for VARMAX models.

Value

A VarmapackModel object.

Simulation

`model$sim(length, nrep = 1L, X0 = NULL, z = NULL, rng = NULL, return_shocks = FALSE)` simulates `nrep` independent series of the supplied length.

For VARMA models, `X0` is optional. If provided, it is an r by $nX0$ matrix or an r by $nX0$ by `nrep` array. Its second dimension must be at least $\max(p, q)$, and its third dimension, when present, must be 1 or `nrep`. Nonstationary VARMA models require `X0`; with MA terms, `Sig` must be positive definite and startup shocks are conditioned on the residual equations implied by the supplied history.

For VARMAX models, `z` is required. `X0` has the same form and its second dimension must be at least $\max(p, q, s - 1)$. It may be omitted when this minimum is zero. The exogenous input `z` is a d by length matrix or a d by length by `nrep` array. Its third dimension, when present, must be 1 or `nrep`.

Pass a `randompack::randompack_rng()` object through `rng` to control the random stream. When it is omitted, Varmapack uses a temporary randomized default Randompack generator. With `return_shocks = FALSE`, the result is an r by length by `nrep` array. With `return_shocks = TRUE`, it is a list with components `X` and `E`, each with that shape.

Model analysis

`model$acvf(maxlag)` returns theoretical VARMA autocovariances, `model$psi(maxlag)` returns impulse-response matrices, and `model$irf(maxlag)` returns orthogonalized impulse-response matrices. `model$specrad()` and `model$ma_specrad()` return the AR and MA spectral radii, respectively. Theoretical autocovariances are not available for VARMAX models with exogenous terms.

Examples

```
A <- matrix(c(0.4, 0.1, -0.2, 0.3), 2, 2)
model <- varmapack_model(A = A, Sig = diag(2))
X <- model$sim(100)

rng <- randompack::randompack_rng()
```

```
rng$seed(123)
X <- model$sim(100, nrep = 3, rng = rng)
```

varmapack_testcase	<i>Create a VARMA testcase model</i>
--------------------	--------------------------------------

Description

Create a built-in named testcase or an unnamed random, deterministic, or spectral-radius-controlled VARMA testcase.

Usage

```
varmapack_testcase(
  which = "random",
  p = NULL,
  q = NULL,
  r = NULL,
  rho = 0,
  rng = NULL
)
```

Arguments

which	A built-in testcase name, a one-based built-in testcase index, or one of "random", "deterministic", and "rho".
p, q, r	Required AR order, MA order, and series dimension for unnamed testcases.
rho	Target spectral radius when which = "rho".
rng	Optional randompack::randompack_rng() used for a random testcase.

Value

A VarmapackModel object.

Examples

```
model <- varmapack_testcase("smallARMA1")
model <- varmapack_testcase("rho", p = 3, q = 1, r = 2, rho = 0.8)
```

varmapack_testcases	<i>List named VARMA testcases</i>
---------------------	-----------------------------------

Description

List named VARMA testcases

Usage

```
varmapack_testcases()
```

Value

A data frame with columns index, name, p, q, and r.

Examples

```
varmapack_testcases()
```

Index

varmapack_autocov, [2](#)
varmapack_cov2corr, [3](#)
varmapack_model, [3](#)
varmapack_testcase, [5](#)
varmapack_testcases, [6](#)